



- Countdown timer
- 1 change over contact
- Maximum runtime 99h 59m 59s
- Easy and quick adjustment of the runtime
- Power fail security
- START/STOP via front button or electrical input (230V)
- Front panel mounting
- Width 48mm



## Technical data

### 1. Function

Countdown timer

### 2. Time range

Adjustment range: 1s to 99h 59m 59s  
Accuracy of reading: 1s

### 3. Indicator

LCD, height numerals 15mm (7,5mm)  
Optical and acoustic signal on completion of time

### 4. Time base

Quartz  
Accuracy:  $\leq \pm 0,1$  sec. / hour

### 5. Mechanical design

Self extinguishing plastic housing,  
IP rating IP20 according to DIN EN 60529  
Protection class II  
Front panel mounting (cut-out 46 x 46mm) with terminal cover  
Type of connection: Plug-in screw terminal

### 6. Supply circuit

Supply voltage: 230V AC  
Rated frequency: 50-60Hz  
Rated consumption: 0,7W

### 7. Input circuit START/STOP

Input voltage: 230V AC (Supply voltage)


### 8. Output circuit

1 change over contact  
Contact material: AgNi  
Switching capacity: 8A / 230V AC with resistive load ( $\cos\phi=1$ )  
6A with inductive load ( $\cos\phi=0,6$ )  
Min. switching power: 300mW (5V / 5mA)

### 9. Environmental conditions

Ambient temperature: -5 to +50°C

## Connections



## Dimensions

